AMMO

Exterior Ballistic Data for British Centerfire Rifle Cartridges

Cartridge	Case length inches	Bullet weight (grs.)	Powder weight (grs.)	Velocity (ft./sec.)			Energy (ft./lb.)			Drop (in.)†	
				Muzzle	100 yd.	200 yd.	Muzzle	100 yd.	200 yd.	100 yd.	200 yd.
*297/230 (Morris) Short	⁹⁄₁₆	37L	1¾ RN	875	720		63	43		15.0	
*297/230 (Morris) Long	¾	37L	2¾ CN	1200	920	760	120	70	48	15.0	71.0
*p240 H&H Apex Flanged	2½	100CP	38½ NC	2800	2570	2355	1740	1470	1230	2.3	10.0
240 Belted Rimless	2½	100CP	40½ NC	2900	2665	2445	1870	1580	1330	2.2	9.2
*242 Rimless Nitro Exp.	2⅜	100CP	42 NC	3000	2740	2490	1970	1635	1355	2.0	8.6
244 H&H Magnum (Belted)	2¾	100CP		3500	3230	2970	2725	2320	1980	1.6	5.1
297/250 Rook Rifle	¹³⁄₁₆	56L	3 CN	1150	940	805	165	110	80	15.5	70.0
256 (6.5mm) Mannlicher	2⅛	160SN	36 NC	2350	2045	1765	1960	1490	1110	3.4	15.5
6.5mm Mann.-Schon.	2⅛	160SN	36 NC	2300	2000	1725	1880	1420	1060	3.6	16.0
275 H&H Magnum (Belted)	2½	160CP	52 NC	2700	2505	2320	2600	2230	1920	2.5	10.5
275 High Velocity (7mm)	2¼	140CP	48 NC	2900	2705	2515	2620	2280	1970	2.2	9.0
276 (7mm) Mauser	2¼	173SN	38 NC	2300	2015	1765	2040	1560	1200	3.9	16.0
p7mm H&H Magnum Flanged	2½	140CP		2650	2450		2184	1867			
*280 Flanged Nitro Exp.	2⅝	140CP	52 NC	2800	2570	2355	2440	2060	1730	2.3	10.0
*280 Flanged Nitro Exp.	2⅝	160HP	52 NC	2600	2300	2020	2400	1880	1450	2.8	12.0
280 Ross Rimless Nitro	2⅝	140CP	54 NC	2900	2665	2445	2620	2210	1860	2.2	9.0
280 Ross Rimless Nitro		160HP	54 NC	2700	2395	2110	2600	2040	1580	2.6	11.5
*280 Jeffery Rimless	2½	140CP	57 NC	3000	2870	2735	2800	2555	2390	2.1	10.0
300 (.295) Rook Rifle	1⅛	80L	4½ CN	1100	915	785	215	150	110	16.5	75.0
300 Sherwood	1½	140L	8½ CN	1400	1195	1060	610	445	350	9.9	44.0
300 H&H Magnum Belted	2¼	150SN	58 C	3000	2660	2350	3000	2360	1835	2.2	9.8
or (30 Super Magnum)		180SN	55 C	2750	2430	2130	3020	2360	1815	2.8	12.5
or (30 Super Magnum)		220SN	49 C	2300	2045	1810	2115	1675	1305	3.9	17.0
p30 Super Flanged H&H	2¹⁵⁄₁₆	150SN	55 C	2875	2581		2755	2225			
p30 Super Flanged H&H		180SN	50 C	2575	2309		2653	2131			
p30 Super Flanged H&H		220SN	46 C	2250	2045		2475	2045			
*30 Purdey Flanged Nitro	2⅝	150SN		2700	2385	2090	2430	1900	1460	2.6	11.5
303 British (Mark 6)	2¼	215S	31 C	2050	1855	1670	2010	1650	1330	4.4	19.0
303 British (Mark 7)	2¼	174S	37 C	2450	2250	2055	2320	1960	1640	3.0	13.0
303 British	2¼	150CP	38 C	2700	2465	2240	2440	2030	1680	2.5	11.0
303 British	2¼	174SN	41 NC	2450	2195	1955	2315	1870	1480	3.1	13.5
303 British	2¼	215SN	31 C	2050	1790	1555	2010	1530	1160	4.6	20.0
310 Cadet	1⅛	120L	6 CN	1200	1010	890	385	270	210	14.0	62.0
318 Rimless Nitro Exp.	2⅜	180CP	55 NC	2700	2395	2110	2920	2300	1780	2.6	11.5
318 Rimless Nitro Exp.		250SN	52 NC	2400	2040	1715	3200	2320	1640	3.3	15.0
333 Rimless Nitro Exp.	2⅜	300SN	65 NC	2200	1960	1720	3230	2540	1980	3.9	17.0
*400/350 Nitro Exp.	2¾	310SN	43 NC	2000	1795	1610	2760	2220	1790	4.7	20.0
350 Rigby Magnum Rimless	2¾	225SN	65 NC	2625	2307		3440	2657			
350 No. 2 Rigby Flanged	2¾	225SN		2600			3400				
*360 Nitro Exp. Flanged	2¼	300SN	30 C	1650	1490	1355	1820	1480	1210	6.9	29.0
*360 Nitro for Black Powd.	2¼	190CT	22 C	1650	1285	1070	1150	700	485	7.6	36.0
o400/360 Purdey Flanged	2¾	300SN	40 C	1950	1776		2537	2102			
o400/360 Westley Richards	2¾	314SN	41 C	1900	1724		2520	2072			
o360 No. 2 Nitro Exp.	3	320SN	55 C	2200	1999		3442	2845			
*369 Purdey Nitro Exp.	2⅝	270SN	64½ NC	2500	2135	1800	3760	2740	1950	3.1	14.0
375 Flanged Nitro Exp.	2½	270SN	40 C	2000	1735	1405	2400	1810	1190	4.9	22.0
o375 Rimless W.R. Nitro	2¼	270SN	43 C	2100	1870		2640	2100			
375 Flanged Magnum Nitro	2½	270SN	59 C	2600	2280	1980	4060	3120	2360	2.8	12.5
375 Flanged Magnum Nitro		300SN	56 C	2400	2105	1825	3850	2960	2220	3.3	14.5
375 Belted H&H Magnum	2⅞	235CP	62 C	2800	2495	2215	4100	3260	2560	2.4	10.5
375 Belted H&H Magnum		270SN	61 C	2650	2325	2020	4220	3250	2450	2.9	12.0
375 Belted H&H Magnum		300SN	58 C	2500	2200	1915	4170	3230	2450	3.0	13.5
450/400 Nitro Exp.	3	400SN	60 C	2100	1845	1610	3920	3030	2310	4.3	19.0
450/400 Magnum Nitro Exp.	3¼	400SN	60 C	2150	1890	1650	4110	3180	2420	4.1	18.0
404 Jeffery Rimless	2⅞	400SN	60 C	2125	1885	1670	4020	3160	2480	4.2	18.0
p416 Rigby Magnum	2⅞	410SN	71 C	2371	2110		5100				
p425 Westley Richards	2⅝	410SN		2350			5010				
450 Nitro Exp.	3¼	480SN	70 C	2150	1900	1665	4930	3860	2960	4.1	18.0
*500/450 Magnum Nitro Exp.	3¼	480SN	75 C	2175	1987		5050	4220			
*450 No. 2 Nitro Exp.	3½	480SN	80 C	2175	1904		5050	3900			
o450 Black Powder Exp.	3¼	310L	120Blk	1800	1510		2240	1570			
o450 Nitro for B.P. Exp.	3¼	365CT	52 C	2100	1809		3578	2655			
577/450 Martini-Henry	2¼	480L	38½ C	1350	1210	1110	1950	1560	1320	10.0	44.0
577/450 Martini-Henry B.P.	2¼	480L	85 Blk	1350	1210	1110	1950	1560	1320	10.0	44.0
465 H&H Nitro Exp.	3¼	480SN	73 C	2150	1830	1620	4930	3580	2800	4.1	18.5
470 Nitro Exp.	3¼	500SN	75 C	2150	1890	1650	5140	3980	3030	4.1	18.0
*475 Nitro Exp.	3¼	480SN	75 C	2175	2000	1830	5040	4260	3580	4.2	18.0
r475 No. 2 Nitro Exp.	3½	480SN	85 C	2200	1925	1680	5170	3960	3020	3.9	17.0
*475 No. 2 Jeffery	3½	500SN	85 C	2150	1880	1635	5140	3930	2970	4.1	18.0
*476 Nitro Exp.	3	520SN	75 C	2100	1925	1760	5085	4295	3585	4.6	20.0
500 Nitro Exp.	3	570SN	80 C	2150	1890	1650	5850	4530	3450	4.1	18.0
*500 Nitro for B.P. Exp.	3	440CT	55 C	1900	1570	1290	3530	2410	1630	5.5	25.0
o500 Black Powder Exp.	3	340CT	136 Blk	1925	1585		2800	1900			
p500 Jeffery Rimless		535SN	95 C	2400			6800				
p505 Gibbs Rimless Magnum		525SN	90 C	2300			6180				
577 Solid Snider	1¾	480L	70 Blk	1250	1055	940	1670	1190	940	13.0	57.0
r577 Nitro Exp.	3	750SN	100 C	2050	1795	1570	7010	5380	4110	4.5	20.0
o600 Nitro Exp.	3	900S	110 C	1950	1650	1390	7600	5450	3870	5.1	23.0

ABBREVIATIONS

†— Drop is computed from horizontal line of departure for the bullet.
*— Available while stocks last; will then become obsolete.
o— Obsolete; no longer available.
r— Re-introduced and again available.
p— Proprietary Cartridge; available only from specific maker.

SN— Soft Nose
CP— Copper Point
CT— Copper Tube
L— Lead
HP— Hollow Point
S— Solid (Jacketed)

BP or Blk— Black Powder
C— Cordite
NC— Nitro-Cellulose
CN— Cadet Neonite
RN— Revolver Neonite

GUN DIGEST (1963) FOLLETT PUBL. CO., CHICAGO

AMMO

BALLISTIC DATA FOR WEATHERBY MAGNUM CALIBERS

Bullets Weight	Bullets Type	Velocity Muzzle	Velocity 100 yds.	Velocity 200 yds.	Velocity 300 yds.	Foot-Pounds of Energy Muzzle	Foot-Pounds of Energy 100 yds.	Foot-Pounds of Energy 200 yds.	Foot-Pounds of Energy 300 yds.	Trajectory* 200 yds.	Trajectory* 300 yds.	Trajectory* 400 yds.
257 Weatherby Magnum: Price, $6.60												
87	SpP	3930	3575	3195	2850	2984	2471	1974	1569	0.5	2.9	6.5
100	SpP	3700	3400	3100	2810	3040	2562	2129	1753	0.7	3.3	7.5
117	RN	3320	2950	2675	2380	2858	2260	1867	1472	1.4	4.4	8.5
270 Weatherby Magnum: Price, $6.60												
100	SpP	3900	3545	3180	2820	3378	2794	2241	1766	0.8	2.7	6.5
130	SpP	3450	3185	2920	2680	3429	2931	2461	2075	1.0	3.6	7.1
150	RN	3240	2905	2590	2300	3489	2820	2234	1761	1.3	5.0	10.1
150	SpP	3240	3010	2800	2600	3489	3018	2612	2252	1.1	3.9	8.3
7mm Weatherby Magnum: Price, $6.60												
139	SpP	3465	3195	2930	2685	3709	3153	2649	2233	1.0	3.3	7.1
154	SpP	3260	3035	2820	2605	3627	3160	2720	2330	1.2	3.8	8.3
175	RN	3067	2790	2500	2270	3662	3024	2429	2002	1.4	5.0	11.5
300 Weatherby Magnum: Price, $7.70												
110	SpP	4050	3625	3230	2835	4007	3218	2543	1970	0.7	2.7	6.6
150	SpP	3630	3360	3095	2850	4389	3753	3193	2706	0.8	3.0	6.7
180	SpP	3350	3115	2895	2685	4477	3882	3361	2892	1.0	3.9	7.5
220	RN	3000	2740	2475	2230	4400	3667	3005	2429	1.5	4.9	11.5
375 Weatherby Magnum: Price, $8.80												
270	RN	2940	2680	2420	2175	5181	4309	3510	2835	1.9	5.5	11.1
300	RN	2800	2510	2270	2025	5223	4197	3432	2745	2.3	6.4	12.5
378 Weatherby Magnum: Price, $15.00												
270	RN	3212	2910	2650	2390	6201	5076	4209	3424	1.4	4.2	8.9
300	RN	3022	2725	2460	2200	6075	4965	4032	3222	1.5	4.7	11.0
460 Weatherby Magnum: Price, $17.50												
500	RN	2725	2480	2240	2025	8245	6830	5570	4550	2.0	7.0	13.3

*Mid-range, with telescope sights.
Bullets—SpP: Spire Point; RN: Round Nose. All cartridges 20 per box.

REMINGTON C.F. PISTOL AND REVOLVER CARTRIDGES—BALLISTICS AND PRICES

CARTRIDGE	BULLET Wt. Grs.	BULLET Style	Muzzle Velocity Feet per Second	Muzzle Energy Ft. Lbs.	Barrel Inches	PRICE Per 50
22 Jet	40	S.P.	2460	535	8⅜	$6.50
25 (6.35 mm.) Automatic	50	M.C.	810	73	2	4.20
30 (7.65 mm.) Luger	93	M.C.	1220	307	4½	5.75
30 (7.63 mm.) Mauser Automatic	85	M.C.	1410	375	5½	5.75
32 Short Colt	80	Lead	795	112	4	3.65
32 Long Colt	80	Lead	790	111	4	3.85
32 Colt New Police	100	Lead	785	137	4	3.85
32 (7.65 mm.) Automatic Pistol	71	M.C.	960	145	4	4.80
32 Smith & Wesson	88	Lead	705	97	3	3.65
32 Smith & Wesson Long	98	Lead	780	132	4	3.85
357 Magnum Hi-Speed	158	M.P.	1430	717	8⅜	6.20
357 Magnum Hi-Speed	158	Lead	1430	717	8⅜	5.45
9 mm. Luger	124	M.C.	1120	345	4	6.00
38 Smith & Wesson	146	Lead	730	173	4	4.50
38 Special	158	Lead	855	256	6	4.60
38 Special	200	Lead	730	236	6	4.80
38 Special	158	M.P.	855	256	6	5.70
38 Special Wad Cutter Targetmaster	148	Lead	770	195	6	4.80
38 Special Metal Penetrating Hi-Way Master	110	Special	1330	433	5	5.85
38 Special Hi-Speed	158	Lead	1085	413	5	5.10
38 Colt New Police	150	Lead	680	154	4	4.50
38 Short Colt	125	Lead	760	160	6	4.05
38 Long Colt	150	Lead	770	197	6	4.50
38 Super Automatic Hi-Speed	130	M.C.	1275	469	5	5.10
38 Automatic	130	M.C.	1040	312	4½	5.10
380 Automatic	95	M.C.	955	192	3¾	4.90
41 Long Colt	195	Lead	730	231	6	5.25
44 Smith & Wesson Special	246	Lead	755	311	6½	6.15
44 Remington Magnum Hi-Speed	240	Ld. G.C.	1470	1150	6½	8.10
44 Remington Magnum	240	S.P.	1470	1150	6½	8.35
45 Colt	250	Lead	855	405	5½	6.15
45 Automatic	230	M.C.	850	369	5	6.55
45 Automatic Wad Cutter Targetmaster	185	M.C.	775	245	5	6.80
45 Automatic Rim	230	Lead	805	331	5½	6.55

norma Ballistics

TEN SHOT AVERAGES
IN 24 INCH BARRELS

Index no.	Cartridge	Bullet Weight grs.	Velocity, feet per sec. V Muzzle	V 100 yds.	V 200 yds.	V 300 yds.	Energy, foot pounds E Muzzle	E 100 yds.	E 200 yds.	E 300 yds.	Max. height of trajectory, inches Tr. 100 yds.	Tr. 200 yds.	Tr. 300 yds.
	.220 Swift												
1	Soft point pointed	50	4111	3611	3133	2681	1877	1448	1090	799	-.2	.9	3.0
2	Full jacket semi pointed	50	4111	3460	2850	2295	1877	1329	902	585	-.2	.9	3.7
	.222 Rem.												
3	Soft point pointed	50	3200	2660	2170	1750	1137	786	523	340	.0	2.0	6.2
4	Full jacket semi pointed	50	3200	2610	2080	1630	1137	756	480	295	.0	2.1	7.1
	.243 Win.												
5	Hollow point	75	3500	3070	2660	2290	2041	1570	1179	873	.0	1.4	4.1
151	Soft point pointed	100	3070	2790	2540	2320	2093	1729	1433	1195	.1	1.8	5.0
148	Full jacket semi pointed	100	3070	2790	2540	2320	2093	1729	1433	1195	.1	1.8	5.0
	.244 Rem.												
7	Hollow point	75	3500	3070	2660	2290	2041	1570	1179	873	.0	1.4	4.1
8	Soft point pointed	90	3200	2850	2530	2230	2047	1624	1279	994	.1	1.6	4.9
	.250 Savage												
9	Soft point pointed	87	3032	2685	2357	2054	1776	1393	1074	815	.0	1.9	5.8
10	Soft point pointed	100	2822	2514	2223	1956	1769	1404	1098	850	.1	2.2	6.6
101	Soft point pointed	120	2645	2405	2177	1964	1865	1542	1263	1028	.2	2.5	7.0
	.257 Roberts												
11	Soft point pointed	100	2900	2588	2291	2020	1868	1488	1166	906	.1	2.1	6.2
12	Soft point pointed	120	2645	2405	2177	1964	1865	1542	1263	1028	.2	2.5	7.0
	6,5 Jap.												
13	Soft point pointed boattail	139	2428	2280	2130	1990	1820	1605	1401	1223	.3	2.8	7.7
14	Soft point round nose	156	2067	1871	1692	1529	1481	1213	992	810	.6	4.4	11.9
	6,5 x 54 MS *												
15	Soft point pointed	77	3117	2731	2369	2036	1662	1274	960	710	.0	1.9	5.6
16	Soft point pointed boattail	139	2580	2420	2270	2120	2056	1808	1591	1388	.2	2.4	6.5
163	Full jacket boattail	139	2580	2420	2270	2120	2056	1808	1591	1388	.2	2.4	6.5
17	Soft point round nose	156	2461	2240	2033	1840	2098	1738	1432	1173	.3	3.0	8.2
164	Full jacket round nose	156	2461	2240	2033	1840	2098	1738	1432	1173	.3	3.0	8.2
	6,5 x 55												
105	Soft point pointed	77	3120	2730	2370	2040	1664	1275	961	712	.0	1.9	5.6
19	Full jacket pointed	93	3150	2705	2292	1920	2050	1512	1085	762	.0	1.9	6.0
20	Soft point pointed boattail	139	2789	2630	2470	2320	2402	2136	1883	1662	.1	2.0	5.6
21	Full jacket boattail	139	2789	2630	2470	2320	2402	2136	1883	1662	.1	2.0	5.6
22	Soft point round nose	156	2493	2271	2062	1867	2153	1787	1473	1208	.3	2.9	7.9
23	Full jacket round nose	156	2493	2271	2062	1867	2153	1787	1473	1208	.3	2.9	7.9
	.270 Win.												
24	Soft point pointed	110	3248	2966	2694	2435	2578	2150	1773	1448	.1	1.4	4.3
25	Soft point pointed boattail	130	3140	2884	2639	2404	2847	2401	2011	1669	.0	1.6	4.7
26	Hollow point boattail	130	3140	2860	2593	2338	2847	2362	1941	1578	.0	1.6	4.8
27	Full jacket boattail	130	3140	2944	2753	2568	2847	2502	2188	1904	.0	1.4	4.3
28	Soft point pointed boattail	150	2802	2616	2436	2262	2616	2280	1977	1705	.1	2.0	5.7
161	Full jacket pointed	150	2802	2616	2436	2262	2616	2280	1977	1705	.1	2.0	5.7



6,5 x 55

"Gun Digest (1963)"

* Apparently stands for
Mannlicher-Schonauer

The nine cartridges below are the only ones that are the equivalent of 6.5 MM. None of them has a bullet weight anywhere near 160 GR.

Western cartridges are identical with Winchester loads having the same basic caliber designation, hence the ballistics given will serve for both brands. Western cartridges not duplicated by Winchester are listed in boldface type. The foregoing also holds true for Remington and Peters loads. Peters cartridges not duplicated by Remington are listed in boldface type.

WINCHESTER C.F. RIFLE CARTRIDGES—BALLISTICS AND PRICES

CARTRIDGE	BULLET		VELOCITY—FT. PER SEC.				ENERGY—FT. LBS.				MID-RANGE TRAJECTORY		
	Wt. Grs.	Type	Muzzle	100 yds.	200 yds.	300 yds.	Muzzle	100 yds.	200 yds.	300 yds.	100 yds.	200 yds.	300 yds.
218 Bee Super Speed*	46	H.P.	2860	2160	1610	1200	835	475	265	145	0.7	3.8	11.5
219 Zipper Super Speed	56	H.P.	3110	2440	1940	1550	1200	740	465	300	0.6	2.9	8.3
22 Hornet Super Speed*	45	S.P.	2690	2030	1510	1150	720	410	230	130	0.8	4.3	13.0
22 Hornet Super Speed*	46	H.P.	2690	2030	1510	1150	740	420	235	135	0.8	4.3	13.0
220 Swift Super Speed	48	P.S.P.	4110	3490	2930	2440	1800	1300	915	635	0.3	1.4	3.8
222 Remington	50	S.P.	3200	2660	2170	1750	1140	785	520	340	0.5	2.5	7.0
243 Winchester Super Speed	80	S.P.	3500	3080	2720	2410	2180	1690	1320	1030	0.4	1.8	4.7
243 Winchester Super Speed	100	Power Pt.	3070	2790	2540	2320	2090	1730	1430	1190	0.5	2.2	5.5
25-20 Winchester High Velocity Super Speed*	60	H.P.	2250	1660	1240	1030	675	365	205	140	1.2	6.3	21.0
25-20 Winchester†*	86	Lead	1460	1180	1030	940	405	265	200	170	2.6	12.5	32.0
25-20 Winchester*	86	S.P.	1460	1180	1030	940	405	265	200	170	2.6	12.5	32.0
25-35 Winchester Super Speed	117	S.P.	2300	1910	1600	1340	1370	945	665	465	1.0	4.6	12.5
250 Savage Super Speed	87	P.S.P.	3030	2660	2330	2060	1770	1370	1050	820	0.6	2.5	6.4
250 Savage Super Speed	100	S.T.Exp.	2820	2460	2140	1870	1760	1340	1020	775	0.6	2.9	7.4
257 Roberts Super Speed	87	S.P.	3200	2840	2500	2190	1980	1560	1210	925	0.5	2.2	5.7
257 Roberts Super Speed	100	S.T.Exp.	2900	2540	2210	1920	1870	1430	1080	820	0.6	2.7	7.0
257 Roberts Super-X	117	S.P.	2650	2280	1950	1690	1820	1350	985	740	0.7	3.4	8.8
264 Winchester Magnum	100	S.P.	3700	3260	2880	2550	3040	2360	1840	1440	0.4	1.6	4.2
264 Winchester Magnum	140	Power Pt.	3200	2940	2700	2480	3180	2690	2270	1910	0.5	2.0	4.9
270 Winchester Super Speed	100	S.P.	3480	3070	2690	2340	2690	2090	1600	1215	0.4	1.8	4.8
270 Winchester Super Speed	130	S.T.Exp.	3140	2850	2580	2320	2840	2340	1920	1550	0.5	2.1	5.3
270 Winchester Super Speed	150	Power Pt.	2900	2620	2380	2160	2800	2290	1890	1550	0.6	2.5	6.3
7x57 m/m Mauser Super Speed	175	S.P.	2490	2170	1900	1680	2410	1830	1400	1100	0.8	3.7	9.5
30-30 Winchester Super Speed	150	H.P.	2410	2020	1700	1430	1930	1360	960	680	0.9	4.2	11.0
30-30 Winchester Super Speed	150	Power Pt.	2410	2020	1700	1430	1930	1360	960	680	0.9	4.2	11.0
30-30 Winchester Super Speed	170	Power Pt.	2220	1890	1630	1410	1860	1350	1000	750	1.2	4.6	12.5
30-30 Winchester Super Speed	170	S.T.Exp.	2220	1890	1630	1410	1860	1350	1000	750	1.2	4.6	12.5
30-30 Winchester Super Speed	170	F.P.	2220	1890	1630	1410	1860	1350	1000	750	1.2	4.6	12.5
30 Remington Super Speed	170	S.T.Exp.	2120	1820	1560	1350	1590	1180	870	645	1.1	5.3	14.0
308 Winchester Super Speed	110	S.P.	3340	2810	2340	1920	2730	1930	1340	900	0.5	2.2	6.0
308 Winchester Super Speed	125	P.S.P.	3100	2740	2430	2160	2670	2080	1640	1300	0.5	2.3	5.9
308 Winchester Super Speed	150	Power Pt.	2860	2520	2210	1930	2730	2120	1630	1240	0.6	2.7	7.0
308 Winchester Super Speed	150	S.T.Exp.	2860	2570	2300	2050	2730	2200	1760	1400	0.6	2.6	6.5
308 Winchester Super Speed	180	Power Pt.	2610	2250	1940	1680	2720	2020	1500	1130	0.7	3.4	8.9
308 Winchester Super Speed	180	S.T.Exp.	2610	2390	2170	1970	2720	2280	1870	1540	0.8	3.1	7.4
308 Winchester Super Speed	200	S.T.Exp.	2450	2210	1980	1770	2670	2170	1750	1400	0.8	3.6	9.0
30-40 Krag Super Speed	180	Power Pt.	2470	2120	1830	1590	2440	1790	1340	1010	0.8	3.8	9.9
30-40 Krag Super Speed	180	S.T.Exp.	2470	2250	2040	1850	2440	2020	1660	1370	0.8	3.5	8.5
30-40 Krag Super Speed	220	S.T.Exp.	2200	1990	1800	1630	2360	1930	1580	1300	1.0	4.4	11.0
30-06 Springfield Super Speed	110	S.P.	3370	2830	2350	1970	2770	1960	1350	900	0.5	2.2	6.0
30-06 Springfield Super Speed	125	Power Pt.	3200	2810	2480	2200	2840	2190	1710	1340	0.5	2.2	5.6
30-06 Springfield Super Speed	150	Power Pt.	2970	2620	2300	2010	2930	2280	1760	1340	0.6	2.5	6.5
30-06 Springfield Super Speed	150	S.T.Exp.	2970	2670	2400	2130	2930	2370	1920	1510	0.6	2.4	6.1
30-06 Springfield Super Speed	180	Power Pt.	2700	2330	2010	1740	2910	2170	1610	1210	0.7	3.1	8.3
30-06 Springfield Super Speed	180	S.T.Exp.	2700	2470	2250	2040	2910	2440	2020	1660	0.7	2.9	7.0
30-06 Springfield Wimbledon Cup	180	F.P.B.T.	2700	2520	2350	2190	2910	2540	2200	1900	0.6	2.8	6.7
30-06 Springfield Super-X	180	M.C.B.T.	2700	2520	2350	2190	2910	2540	2200	1900	0.6	2.8	6.7
30-06 Springfield Super Speed	220	Power Pt.	2410	2120	1870	1670	2830	2190	1710	1360	0.8	3.9	9.8
30-06 Springfield Super-Speed	220	S.T.Exp.	2410	2180	1980	1790	2830	2320	1910	1560	0.8	3.7	9.2
300 Savage Super Speed	150	Power Pt.	2670	2350	2060	1800	2370	1840	1410	1080	0.7	3.2	8.0
300 Savage Super Speed	150	S.T.Exp.	2670	2390	2130	1890	2370	1900	1510	1190	0.7	3.0	7.6
300 Savage Super Speed	180	Power Pt.	2370	2040	1760	1520	2240	1660	1240	920	0.9	4.1	10.5
300 Savage Super Speed	180	S.T.Exp.	2370	2160	1960	1770	2240	1860	1530	1250	0.9	3.7	9.2
300 H. & H. Magnum Super Speed	150	S.T.Exp.	3190	2870	2580	2300	3390	2740	2220	1760	0.5	2.1	5.2
300 H. & H. Magnum Super Speed	180	S.T.Exp.	2920	2670	2440	2220	3400	2850	2380	1970	0.6	2.4	5.8
300 H. & H. Magnum Super Speed	220	S.T.Exp.	2620	2370	2150	1940	3350	2740	2260	1840	0.7	3.1	7.7
303 Savage Super Speed	190	S.T.Exp.	1980	1680	1440	1250	1650	1190	875	660	1.3	6.2	15.5
303 British Super Speed	180	Power Pt.	2540	2300	2090	1900	2580	2120	1750	1440	0.7	3.3	8.2
303 British Super Speed	215	S.P.	2180	1900	1660	1460	2270	1720	1310	1020	1.1	4.9	12.5
32-20 Winchester High Velocity Super Speed*	80	H.P.	2100	1430	1090	950	780	365	210	160	1.5	8.5	24.5
32-20 Winchester (Oilproof)†*	100	Lead	1290	1060	940	840	370	250	195	155	3.3	15.5	38.0
32-20 Winchester (Oilproof)*	100	S.P.	1290	1060	940	840	370	250	195	155	3.3	15.5	38.0
32 Winchester Special Super Speed	170	Power Pt.	2280	1870	1560	1330	1960	1320	920	665	1.0	4.8	13.0
32 Winchester Special Super Speed	170	S.T.Exp.	2280	1870	1560	1330	1960	1320	920	665	1.0	4.8	13.0
32 Remington Super Speed	170	S.T.Exp.	2120	1760	1460	1220	1700	1170	805	560	1.1	5.3	14.5
32-40 Winchester	165	P.S.	1440	1250	1100	1030	760	570	445	390	2.4	11.0	28.0
8x57 m/m Mauser Super Speed	200	Power Pt.	2320	1990	1720	1500	2390	1760	1310	1000	0.9	4.4	11.5
338 Winchester Magnum	200	Power Pt.	3000	2690	2410	2170	4000	3210	2580	2090	0.5	2.4	6.0
338 Winchester Magnum	250	S.T.	2700	2430	2180	1940	4050	3280	2640	2090	0.7	3.0	7.4
338 Winchester Magnum	300	Power Pt	2450	2160	1910	1690	4000	3110	2430	1900	0.8	3.7	9.5
348 Winchester Super Speed	150	S.T.Exp.	2890	2460	2060	1710	2780	2020	1410	975	0.6	2.9	7.9
348 Winchester Super Speed	200	S.T.Exp.	2530	2220	1940	1680	2840	2190	1670	1250	0.9	3.6	9.0
348 Winchester Super Speed	250	S.T.Exp.	2350	1970	1660	1410	3060	2150	1530	1100	0.9	4.4	11.5
35 Remington Super Speed	200	Power Pt.	2100	1710	1390	1160	1950	1300	860	605	1.2	6.0	16.5
35 Remington Super Speed	200	S.T.Exp.	2100	1710	1390	1160	1950	1290	865	605	1.2	6.0	16.5
351 Winchester Self-Loading (Oilproof)*	180	S.P.	1850	1560	1310	1140	1370	975	685	520	1.5	7.8	21.5
351 Winchester Self-Loading (Oilproof)*	180	F.P.	1850	1560	1310	1140	1370	975	685	520	1.5	7.8	21.5
358 Winchester Super-Speed	200	S.T.	2530	2210	1910	1640	2840	2160	1610	1190	0.8	3.6	9.4
358 Winchester Super Speed	250	S.T.	2250	2010	1780	1570	2810	2230	1760	1370	1.0	4.4	11.0
375 H. & H. Magnum Super Speed	270	Power Pt.	2740	2460	2210	1990	4500	3620	2920	2370	0.7	2.9	[illegible]
375 H. & H. Magnum Super Speed	300	S.T.Exp.	2550	2280	2040	1830	4330	3460	2770	2230	0.7	3.3	8.3
375 H. & H. Magnum Super Speed	300	F.P.	2550	2180	1860	1590	4330	3160	2300	1680	0.7	3.6	[illegible]
38-40 Winchester (Oilproof)*	180	S.P.	1330	1070	960	850	705	455	370	290	3.2	15.0	[illegible]
38-55 Winchester	255	S.P.	1320	1160	1050	1000	985	760	625	565	2.9	13.0	[illegible]
44 Magnum Super-X	240	H.S.P.	1750	1350	1090	950	1630	970	635	480	1.8	9.4	[illegible]
44-40 Winchester (Oilproof)*	200	S.P.	1310	1050	940	830	760	490	390	305	3.3	15.0	[illegible]
45-70 Government	405	S.P.	1320	1160	1050	990	1570	1210	990	880	2.9	13.0	[illegible]
458 Winchester Magnum Super Speed	500	F.P.	2130	1910	1700	1520	5040	4050	3210	2570	1.1	4.8	[illegible]
458 Winchester Magnum Super Speed	510	S.P.	2130	1840	1600	1400	5140	3830	2900	2220	1.1	5.1	[illegible]

†Inside Lubricated H.P.—Hollow Point O.P.E.—Open Point Expanding S.P.—Soft Point P.S.P.—Pointed Soft Point F.P.—Full Patch S.T.—Silvertip M.C.B.T.—Meta

*50 per box F.P.B.T.—Full Patch Boat Tail H.C.P.—Hollow Copper Point

Courtesy Weste

"Gun Digest (1963)"